

FM 410 HP 4*2 Tractor

FO Number / OM Number		Print date
2805-50-80561 / 15080561		2019-08-16
Chassis Number	VIN Number	
B-755484	YV2XZ22A4GB755484	
Build week	Confirmed delivery day	Planned arrival date
201549	2015511 (YYYYWWD)	
Latest update		
2016-01-08 (YYYY-MM-DD)		
Chassis Unique Homologation Document		General Homologation Document
COC (EU) (weight calculation performed) State Certno WVTA.csv LEGCHECK		<ul style="list-style-type: none"> Volvo Powertrain RMI statement Volvo Truck RMI statement COP Statement
Supplementary drawing(s):		
<ul style="list-style-type: none"> FM - Front Mounted Equipment TYPE-FM_BUMP-B_FrontMountedEquipment.zip TYPE-FM_BUMP-B_FrontMountedEquipment.jpg REAR FENDER 3200301.dxf 3200301.pdf BODY ATTACHMENT 3200308.dxf.zip 3200308.pdf TRAILER CONNECTION 3200309_3.dxf.zip 3200309_3.pdf AD-BLUE TANK 3200344.dxf.zip 3200344_2.pdf EXHAUST SYSTEM 3200372_02.dxf.zip 3200372_02.pdf UNDERRUN PROTECTION, SIDE 3200383_3.dxf.zip 3200383_3.pdf CAB-HSLP 3200395[1].dxf.zip 3200395[1].pdf 		
Tyres front		Tyres rear
315/70R22.5 GOODYEAR FUELMAX S HL		315/70R22.5 GOODYEAR FUELMAX D

Customer Adaptations

CA No.	Description	Change Description
S93727	Special bracket for Polish fire extinguisher (std position, driver seat) (*)	Show

(*) IMPORTANT: If order is built with customer adaptations, final specification may differ from the information presented here, please check with [local support](#) or [TSSC](#) for further information.

 Latest updates

Technical Specification

ADMINISTRATION	
Variant	Description
BC-FM	FM model for Business Control
UASAFE	Without active safety package
FM42T410	FM 410 HP 4*2 Tractor
PL-22120	Volvo Tuck Center Mlochow
UVISI	Without Visibility package
MEDIAIR	Medium chassis height with rear air suspension
EPAM342	EUD ADJUSTM FM13 42
ULSA	Without local sourcing
USWUR	Remote software upgrade disabled
UDFFAM	Without Fuel Advice
UDRUT	Without My Truck app
S93727	Special bracket for Polish fire extinguisher (std position, driver seat)
TC-LONGD	Long distance transport cycle (driving pattern)
MFACTBEL	Main Factory Belgium
EU6SCR	Turbo-S Euro 6 emission level with SCR, particulate filter and EGR
UPEPROT	Without personal protection package
DF-FUELM	Dynafleet Fuel & Environment service, monthly subscription
UDFDTM	Without Dynafleet Driver Times service
DF-POSM	Dynafleet Positioning service, monthly subscription
UDFMSG	Without Dynafleet Messaging service
POL	Market Poland
WB3500	Wheelbase 3500 mm
24-HDV	New generation Volvo heavy vehicle
FM 42 T	FM 4x2 Tractor
DIRT-MED	Medium dirty roads/surfaces

EGR-H	Exhaust gas recirculation, hot
TYPE-FM	FM Low tilt cab
WVTA-EC	Whole Vehicle Type Approval, EC
4*2	4*2 - Two axles, rear axle driving
TRACTOR	Tractor model
RC-SMOOTH	Smooth road conditions
GCW44.0	Gross combination weight 44.0 tonnes
ENG-VE11	10.8 litre six cylinder engine
VH3.8	Total vehicle height max. 3.8 metres
RAL13	Rear axle load 13 tonnes
STWPOS-L	Left hand drive
VW2600	Vehicle width 2600 mm
FAL7.5	Front axle load 7.5 tonnes
ADR2	ADR adaptation - transportation of dangerous goods, 2 switches (1 in dash, 1 outside on cab back)
MA-BAS	Basic market adaptation
CHH-MED	Chassis height medium - approx. 900 mm above ground level
ALTI2500	Altitudes up to 2500 metres above the sea level
COG-BAS	Complete superstructure & payload centre of gravity between 0.5 m and 1.0 m above top of truck frame
CURV-L	Low curve density (the speed is seldom reduced due to driving in curves)
VUPT-A2	Vehicle uptime, automatic service activation, weekly download, setting 2
NR-80EC	EC external noise requirement 80 dB(A)
ADRC-FL	FL ADR classification covering FL, EXII, EXIII, & AT classes (printed on ADR label UN ECE R105)
LEGC	Legislation check enabled for order
B-TANK	Tanker (gas, liquid, slurry)
ULHE1	Without tail lift
ULHE2	Without crane
ULHE3	Without snow plough
ULHE4	Without miscellaneous load handling equipment
T-PFLAT	Predominantly flat topography
VASSIS2	Vehicle assistance service enabled, with voice channel
RFUEL	FICTIOUS VARIANT RIGHTHAND FUELTANK (ALL SIZES)
WVTA	Whole Vehicle Type Approved
RT-AL	Brushed aluminium rims with std holes (long stud fixing) on all axles
F315-70A	Front axle tubeless tyre 315/70R22.5
D315-70A	Drive axle tubeless tyre 315/70R22.5
UPHTRI10	Seat black embossed text insert, black vinyl bolster&blue vinyl side ins&text int in match grey/blue
ESH-REAR	Horizontal muffler, rear exhaust outlet
ULHFPV	Without long haul vehicle fuel package
FM-HSLP	FM Globetrotter sleeper cab
ULHFPS	Without long haul fuel package (service)
URESTING	Without sleeping/resting package
UTLHFUEL	Without total long haul fuel offer
AUDHIG	High power aud syst. RDS radio/CD,ant.,6 speak,integr bluet ph, USB/Line. Prep/Dynafi office portal.
UAIRPACK	Without airflow package
URH	Without roof hatch
UL-FUEL	Without left diesel tank
R330A71	Right 330 litre aluminium 710 mm high D-shaped diesel tank
MIRC0FM	El heat&oper main rear view mirr, el heat wide angle mirr (both sides). Close view mirr pass side.
UDRIVE	Without driving package
1DAYDIG	One day digital tachograph, EC approved
POL-MSP	Poland

ENGINE WITH MOUNTING AND EQUIPMENT

Variant	Description
PRIM-MAN	Manual priming pump for fast and easy bleeding of the fuel system
TURBO-S	Turbo single stage
UWILDBAR	Without wild bar
UFTI	Without fuel tanks interconnection
OILS-PL	Plastic oil sump
TURB-B	Basic turbo
HS-BAS	Basic muffler heat shield for all emission variants
CCV-OX	Closed crankcase ventilation with oil separator and a maintenance free gas centrifuge
ADTP-R	AdBlue tank on right hand side
UADTC	Without AdBlue tank cover
OBDEC1	High emission level consequences
OBDEP-B	EU6 mandatory on board diagnostics, phase B regulations
BUGNET	Radiator screen / Mosquito net (PVC coated fibreglass) in front of radiator
D11K410	Diesel engine, 10.8 litre Euro 6 SCR + EGR (Diesel Particulate Filter), 410 hp, 1950 Nm
ETOR1980	Engine torque range 1911 - 1980 Nm
EBR-VEB	Volvo Engine Brake, VEB (compression brake with exhaust pressure governor, EPG)
EAP-LHD2	Light heavy duty engine application (std pistons and corrosion resistant valve seats)
AF-R	Hot fuel recirculation heated fuel filter
USPEEDDU	Without dual speed limiter
SPEED90	Road speed limiter setting 90 km/h, EC
CRUISEC	Basic cruise control with controls in steering wheel

AIRIN-HI	High air intake
ENGPROT	Engine protection
FUELTS71	D-shaped 710 mm diam fuel tank
TNK-SING	Single mounted fuel tank
FTANK-AL	Aluminium fuel tank
FCAP-L	Lockable diesel and AdBlue tank caps
STRAP-P	Painted fuel tank straps
UEXST	Without vertical exhaust
UEXSH	Without extra exhaust heat shield
EAS-SD	Selective Catalyst Reduction + Diesel Particulate Filter, ceramic
EM-EU6	Emission level Euro 6
ACL1ST	Air cleaner with one filter element
DRC-AUTO	Regeneration control of diesel filter particulates - fully automatic (in motion)
URSPED	Without remote speed limiter
USPLIMS	Without speed limiter sensor
SCRS-EHH	Electrically heated SCR system equipment
PADB80	80% AdBlue filling in tank
CPSR-VAR	Variable coolant pump speed ratio
EASO-H	Horizontal orientation of the aftertreatment system
UTFUEL	Without temporary diesel tank
ADB064	AdBlue tank usable volume 64 litres
FUEFE2LW	Large engine mounted dual fuel filter with water separator and drain. For poor fuel (outside WestEu)
UXFUEL	Without extra fuel filling
ATL25	Ambient temperature down to -25 degrees C
ATU40	Ambient temperature up to +40C
FUFF-AS	Fuel filling anti-spillage device
UFUEQWH	Without fuel line heater
DIESEL	Diesel fuel
FTCL-BAS	Fuel tank with basic ground clearance

ELECTRIC POWER SUPPLY, LIGHTING, INSTRUMENTS

Variant	Description
HL-BASIC	Halogen H7 head lamps
TEMP-TRA	Transmission lubricant temperature gauge
24AL120B	Alternator 120 Ampere
SI-GRAF	Speedometer instrument, tachograph
1DAY-STD	1 day tachograph, EC
CALI-DIG	Digital calibration of tacho. & speedometer
BATTD128	Battery density, 1.28 acid solution
ASSIST4	Assistance switch and microphone, Volvo Action Service (VAS)
HWSS-FCB	Forward collision warning (stationary and moving objects) with emergency braking
UARLIG	Without additional rear lights
URSENSW	Without wiper rain sensor
TAS-DIG	One day digital tachograph. EC approved, compliant with annex 1B regulation.
INLI-BAS	Interior white light with smooth light transition at on/off, no dimming
URESTS	Without reflecting white stripes on chassis side
UALCOLOC	Without alcolock
SID-BAS	Dashboard integrated monochrome information display, 75 x 735 pixels / 150(W) x 30(H) mm
EWT3500	Equivalent wheelbase turning, 3500 mm
BLIGHT-B	Basic brake light
UBATTREC	Without battery reconditioner
URPLCR	Without rear position lamp
BBOX-L	Battery box on left hand side
2BATT225	Batteries 2x225 Ah
24V	Electrical system 24V
UDAS	Without Driver Alert Support (without drowsy driver warning)
UPHONE	Without telephone or telephone preparation kit
HL-ASYMR	Headlamp alignment set for right hand traffic
UDETECTS	Without smoke detector in cab
HORN-ELS	Single electrical front horn
HORN-F1S	One front mounted (behind grille) single tone air horn, Jericho. Operated by steering wheel buttons.
URTOLL	Without road toll equipment
USOUTLET	Without electrical outlet in sleeper compartment
FMS-PK	Fleet Management System gateway, preparation kit
TWEETER	Tweeter
ECBB-BAS	Body builder electrical centre without any body builder module
POSLMP-W	Two white front roof mounted position lamps (end outline marker lamps, LED on FH)
UASL	Without spot lamps in sign box
WWF-ALC	Windscreen washer fluid with alcohol additive
WL-TA1W	Trailer arch working lamp with white lens and LED/70W bulb
UDAE	Without vehicle data analysis equipment
UWARNLIG	Without roof mounted beacon warning lamp
SPG-KM	Speedometer scale kilometres per hour
EST-AID	Engine start pre-heating element
TL-BAS	Basic tail lights with bulbs

MSWI-A	ADR main switch - ADR switch circuit shut down
FOGL-WC	White front fog lamps
DRIVL2	Two auxiliary front driving lamps
UAUXL	Without snow plough preparation kit
UHLADJ	Without headlamp adjustment
UHLCLEAN	Without headlamp cleaner
IMMOBIL	Immobiliser
UIDLAMP	Without identification lamps
MARKL-SR	Side and rear marker lights
USRL	Without chassis working lamps
DIFL-POL	Driver information first optional language - Polish
DISL-DEU	Driver information second optional language - German
UKEYB	Without keyboard
USAS	Without Service Alert System
UAMPL	Without external amplifier
UCLSTAT	Without cornering lights
UBAMAFRE	Without enhanced flooded batteries
UBEPREP	Without body builder software electrical preparation
UWLC	Without working lamps back of cab
TD-LED	Trailer detection with LED sensor
UAHS	Without automatic headlamp switching
UBBCHAS	Without Body builder electrical interface
TLB-BAS3	Fender mounted tail lamp bracket
ANT-CBR	Right hand side roof mounted foldable antenna and cables for CB radio, single aerial.
SPK-DDR	Loudspeakers in dash, doors & rear
AIP-BT	Audio integrated handsfree bluetooth phone
ACON-USB	USB audio communication connector
XCON-AUD	Audio AUX Line in connector
UAESW	Without Body builder electrical switches
TGW-3GWL	Telematics gateway with 3G modem and WLAN
UHLPPRO	Without headlamp protection
UREMCON	Without wireless remote control
BUPALARM	Back-up alarm
ARL-FLEX	Two (driver and passenger side) reading lamps with flexible arms and led lamps fitted on side walls
UINFOT	Without TV mounting preparation kit
UTESP	Without Driver Service Platform
UBUPMON	Without back-up monitor
UDRID	Without telematics driver ID with USB
LSS-DW	Lane keeping support - lane departure warning system
ULCS	Without Lane Change Support
UARSL	Without additional road speed limit
AUDWB1	Audio wavebands FM 87,5-108,0 MHZ, AM 522-1611 KHZ
UMAPR	Without map region for navigation
UBULBKIT	Without bulb and fuse kit
UEIDLESD	Without engine idle shutdown
ULAMPIN	Without inspection lamp
USPOTP	Without spotlight preparation
ULOADIND	Without load indicator
UCOMEQ	Without communication equipment
TAMA-B	Tachograph preparation kit for basic market area
UALARMB	Without burglar alarm
UAUXSW	Without wiring for extra switches
INST-MED	Medium level instrument cluster - 4 inch colour display 240x320 pix
AUD-CDM	Radio with CD player, MP3 capability
UBATTMAN	Without battery control (displays voltage)
DRL-LED	V-shaped ("V-light") day running light (LED).

POWER TRANSMISSION

Variant	Description
TRAP-BAS	Basic gearbox application
APF-BAS	Basic I-shift PTO functions
RSS1344C	Rear single reduction solo axle - axle load 13 tonnes, GCW 44 tonnes, version C
CS43B-O	Single plate clutch, plate diameter 430 mm
TRA-AMT	Automated mechanical gearbox
GSS-AGS	I-shift lever gear selector
AT2412E	VPT AUTOMATED TRANSMISSION 2400NM 12SPEED
UPTER	Without rear engine mounted PTO
UTCOOL	Without transmission cooler
UPTOENGR	Without rear engine mounted PTO
UPTOTR	Without gearbox driven power take-off
RAT2.85	Rear axle ratio 2.85
PROPS-M	Propeller shaft dimension medium, single joint
PSM1	Propeller shaft manufacturer Dana Spicer
DL-FULL	Differential lock between axles and wheels
UEPTT	Without engine power take-off torque capacity

UTPTT	Without gearbox power take-off torque capacity
AMSO-BAS	I-shift basic gear shifting without kickdown
AVO-BAS	Basic I-shift application software
TP-DICON	I-shift Distribution and Construction optimized gear changing software
SRED-V	Single reduction rear axle

BRAKE

Variant	Description
UCLUAIRC	Without clutchable air compressor
PBREL-A	Automatic parking brake release
TEC-DET	Detachable trailer electric cable
TBC-EC	Trailer brake connection, European Community
TREL15	15 pol electrical trailer connector (ADR certified)
PNPROT	Protective cover for chassis mounted pneumatic equipment
TBH-COL	Long coiled trailer brake hoses (4000 mm)
EBS-MED	EBS (Electronic Brake System) medium package
UTRBSTRE	Without low speed automatic trailer brake activation (stretch brake)
PDC-IF	Pneumatic distribution center location - inside frame
UPBRAD	Without pusher axle disc brake dimension
UTRACON	Without trailer light converter
UTABS	Without trailer ABS circuit converter
ATANK-AL	Aluminium air tanks
BF-DIBAS	Disc brakes with solid discs
FBRA-D43	Front axle disc brake diameter 430 mm
UTBRD	Without tag axle brake
RBRA-D43	Drive axle disc brake diameter 430 mm
UTBRA	Without tag axle brake dimension
BSYS-EBS	Electronic brake system
DBRDUST	Dust shield for rear brakes
AUXPARK	Two extra parking brake chambers
BRAKE-DV	Disc brakes
ATNK-GEN	Air tank capacity, standard
FBREG-E	Front axle regulating brake valve for EBS
SIL-BRV	Brake valves silencer
URETARD	Without retarder
UAUXATNK	Without extra air tank
2COMP900	Dual cylinder air compressor 636 cc
TRBRAKE	Trailer brake valve
TCP-BMC	Trailer connection bracket (steel arch) mounted back of cab
TRBR-STA	Stationary trailer brake control
ABS	Lock free brakes
ESP-BAS1	Electronic Stability Program (ESP), package 1

WHEEL SUSPENSION AND STEERING

Variant	Description
PSP-FIX	Power steering pump with fixed displacement
STW-D450	Steering wheel with diameter 450 mm
U1PAC	Without first pusher axle capacity
U1TAC	Without first tag axle capacity
STWM-BAS	Standard steering wheel material
FAT-RIG	Conventional front axle suspension
RAD-GR	Rear air suspension, 1 axle - 1 driven
FA-MED	Front axle medium ground clearance
FAA10	One front axle, not driven
URSTS	Without rear steering system
UACTST	Without active steering
UBL	Without bogie load sharing
UAUXPSP	Without extra power steering pump
URVCERT	Without vehicle certification, road
UBCYLPRO	Without brake cylinder protection
STG20.0	Steering gear ratio 20.0
PSS-SING	Single power steering system
STGW-ADJ	Mechanically adjustable steering wheel
ULDFA	Without load distribution on front axles
URALIM	Without first rear drive axle load limiter
ULIFT	Without bogie lift

FRAME, SPRINGS, DAMPING AND WHEELS

Variant	Description
WTDF22.5	Front wheel and tyre inner diameter 22.5 inches
WTDD22.5	Drive wheel and tyre inner diameter 22.5 inches
UWTD	Without tag axle wheel and tyre inner diameter
UTWT	Without tag axle wheel type
UWTTM	Without tag axle wheel and tyre mounting
WMF-AL	Front aluminium rims
WMD-AL	Drive aluminium rims
UWMT	Without tag axle rim material

WDF900	9.00 inch front axle rims
WDD900	9.00 inch drive axle rims
UWDT	Without tag axle wheel dimension
UINFLAHO	Without tyre inflation hose
UTIREPM	Without tyre pressure monitoring
UTT	Without tag axle tyre
TMF-GOOD	Goodyear front axle tyre
TMD-GOOD	Goodyear drive axle tyre
UTMT	Without tag axle tyre
TR-EUR	Tyre region Europe (EU and EFTA)
ASF-DL1	Air suspension with 1 driving level
UGUARD	Without guard plate for cooling pipes and oil sump
USPWCAT	Without spare wheel carrier
USPWCARR	Without spare wheel carrier
USPWT	Without spare wheel with tyre
FSI-LEAF	Front leaf suspension
UGAUGETP	Without tyre pressure gauge
URUPP	Without rear underrun protection pos.
WTA-TL	tubeless tyres
UTMPR	Without pusher axle tyre
RSL5-BAS	Rear air suspension basic levelling stroke
XMBRR-B	Basic rear crossmember closing
WTD-DUAL	Dual mounting of drive axle wheel and tyre
UMRUP	Without rear underrun protection
FSM-MF	Maintenance free front suspension
UWCAP	Without wheel caps
USUPS	Without steps in side underrun protection
UTRTT	Without tag axle tyre tread
UPTT	Without pusher axle tyre tread
FUP	Front underrun protection
UWTDTP	Without wheel and tyre diameter on pusher axle
UFRF	Without frame rail clearance
RSAP-BAS	Standard rear suspension application (without reinforcements)
UFALIM	Without front axle load limiter
PROTC-I	Improved corrosion protection level
UTWP	Without pusher axle wheel type
UWDP	Without pusher axle wheel dimension
URESTRUP	Without reflecting red stripes on rear underrun protection
UFRACLOS	Without frame end closing
TXMB4827	Transmission crossmember web location (main 4827)
RFEC-B	Rear frame end, bent (standard for tractor vehicles)
XMBT-B	Basic transmission crossmember
FST6565	Frame section thickness - web 6.5 mm / flange 6.5 mm
FRAME266	Frame rail section external height 266 mm
RFL825	Rear frame length 825 mm from 1st drive axle
URUP	Without rear underrun protection
FST-PAR1	1 leaf front parabolic suspension (normal stiffness)
RST-AIR	Rear air suspension
FSS-LEAF	Front leaf suspension
RSS-AIR	Rear air suspension
FSTAB2	Front stabilizer with medium high stiffness
SUP-BAS	Standard aluminium bars for side underrun protection
RSTAB1	Rear stabilizer with normal stiffness
UFIL	Without frame inner liner
SUSPL-EC	Air suspension levelling with electronic control

BODY, CAB AND INTERIOR

Variant	Description
UEBHEAT	Without electrical engine block heater
FMUDE-B	Front mudguard extension, basic
UCSPL	Without storage in lower center dash panel
ARU-BAS	Vinyl armrest upholstery
GRABHI-B	Steel instep grab handle
UCPR	Without cab roof protection
UBUMPSP	Without front bumper spoiler
UTBL	Without left toolbox
UTBR	Without right toolbox
SBPRE-DS	Driver seat belt pretensioner
JACK-12T	Jack 12 tonnes
TOOL-BAS	Basic tools (combination screw driver, socket wrench)
URUSTP	Without transport rust protection (wax) except for muffler strap connections
DGLAS-H	Tempered door glass
UCOFMAK	Without coffee maker
USTUC	Without storage compartment under cab
UWRNLAMP	Without portable warning lamp

USBPREPS	Without passenger seat belt pretensioner
<u>1519RED</u>	<u>Cab colour solid Delhi Red / Solid clear coat = 7519RED</u>
<u>PAICS-B</u>	<u>Basic painting in a lightning grey colour of mirror housings, insteps and bumper</u>
ULADDER	Without ladder back of cab
KEYF4336	Keyfob frequency channel 433.6 MHz
EMBL-MO	Mounted emblems
UBOTTLEH	<u>Without bottle holder</u>
UMICROWV	Without microwave equipment
SUPH-T1	<u>Seat upholst.-black striped text. insert, black smooth text. bolster&red(FH)/blue(FM)vinyl side ins.</u>
SEATBRIA	Seat belt reminder in instrument, with audio
UTABLE	Without foldable table
<u>CABPT-R1</u>	<u>One front cab roof pass through on passenger side</u>
UWARVEST	Without warning vest
<u>AIRBAG</u>	<u>Airbag on driver side</u>
URUS	<u>Without rear cab upper storage</u>
UOLMAT	<u>Without overlay mattress protector</u>
<u>WRITEPAD</u>	<u>Writing pad with spring-loaded paper clip</u>
USIGNS	Without green and safe signs in front
URLS	Without storage under bunk
UVANMIR	Without vanity mirror
DIMPLATE	Dimension plate, EC
<u>MATL-FI</u>	<u>Mattress lower bunk - firm for over approx. 100 kg, pocket springs.</u>
DLAY-BAS	Basic dashboard layout
<u>DTRI-SKY</u>	<u>Dashboard in light beige/skylark</u>
TOP2	Transmission oil STD 1273,07. Synthetic, thin oil. Needs filtering and cleaned transmission.
UCFAFS	Without foldable extra front cab foot-step
HCC-EXT	Unlockable front lid - Exterior hood catch control
<u>SBD-RED</u>	<u>Red safety belts, passenger and driver seats</u>
SBP-RED	Red safety belt, passenger seat
UADH	Without roof aerodynamic device height
UCPARKC	Without cab parking cooler
UADCF	Without additional flap on chassis fairings
UAIDKIT	<u>Without first aid kit</u>
<u>ISUNF-MD</u>	<u>Interior front plastic sun visors (driver and passenger side) with mirror on driver side</u>
UAUXFS	Without extra cab side foot-step
SIMC1	Sim card, Telenor SE
CSPT-T	Center section dashpanel top, tray
UPUBS	<u>Driver's handbook only in local language</u>
<u>EXTL-BAS</u>	<u>Basic exterior finish in a lightning grey colour of mirror housings, insteps and bumper.</u>
<u>UTBUNK</u>	<u>Without top bunk</u>
UIDLMPSW	Without switch for identification lamps
<u>CSPU-S</u>	<u>One open storage (behind push open lid) in upper part of dash panel center section</u>
UAWINDR	Without rear window
UROHO	<u>FH: Non opening sky window (tinted glass)/emergency exit (with emerg hammer). FM: Without roof hatch</u>
<u>CSGN-GTR</u>	<u>GLOBETROTTER decal in the cab roof sign area</u>
EMI-EMBL	Emission emblems
CAB-HSLP	High sleeper cab
<u>RCABS-M</u>	<u>Mechanical rear cab suspension</u>
<u>CTILTP-M</u>	<u>Manual cab tilt pump</u>
UADFS	Without extra DIN slots in front shelf (blind slots)
FMUD-AS	Mudflaps with anti-spray on all front axle fenders
USIDESTP	Without side foot-step and handle
<u>FCABS-M</u>	<u>Mechanical cab suspension</u>
UAWINDS	Without rear side window
<u>WLIFT-EB</u>	<u>Electrical window lift</u>
URHATCH	Without roof hatch
<u>GLAS-TIN</u>	<u>Tinted windows (front/side/rear)</u>
<u>LBK70</u>	<u>Lower fixed bunk, not foldable - 2000x700 mm. Safety net included.</u>
FMAT-RUB	<u>Two black rubber floor mats</u>
<u>PST-STD2</u>	<u>Passenger seat, regular, non suspended</u>
CABH210	Cab height 210 cm
UACCBKRT	<u>Without roof mounted accessory bracket</u>
UREFS	<u>Without reflecting stripes on cab</u>
LANG-EG	English/German text on decals/signs
PUBL-POL	Polish publication language
CERT-POL	Certification labels for Poland
<u>LOCK-REM</u>	<u>Central door locking with remote control</u>
UREFL	Without reflectors
<u>DPAN-LU</u>	<u>Door panel in smooth dark blue metallic vinyl</u>
UMATINS	Without insert mat on engine tunnel
AMIR-WB	Wide angle mirror on both sides
<u>AMIR-F20</u>	<u>Front close view mirror above windscreen, passenger side (radius 200 mm)</u>
TRIM-GN	Textile interior trim in matching grey nuances
<u>ARMRE-DB</u>	<u>Two armrests on driver seat</u>

UROSIL	Without illuminated roof sign
DST-CF4	Driver seat, comf, susp, belt
UFIREXT	Without fire extinguisher
PH-CAB2	Cab parking heater, 2 kW
AMIR-S30	Close view mirror on passenger side, radius 300 mm
ISUNS-DS	Manually manoeuvred side interior sun visor (roller blind type) on driver side
UAS	Without extra shelves in front rollfront compartments
CU-MCC	Electrical manually controlled air conditioning
UACU	Without additional climate unit
UDFHFP	Without Dynafleet Positioning+ service
BUMP-B	Plastic front bumper
TOWF-NO1	One front towing device
UWINREP	Without cab side window replica
BEDNET	Lower bunk safety net
USAFETYB	Without safety box
MPLA-ENG	Manufacturing plate, English version
SLCP-BAS	Basic sleeper control panel (controlling interior light, parking heater, roof hatch and door lock)
SUNV-H	Exterior transparent dark grey front sun visor
UXSEACAB	Without extra cab sealant material for dust tightness
UADROOF	Without roof air deflector
UADSIDE	Without cab side air deflectors
UADCHAS	Without chassis side skirts
WARNTRI2	Two warning triangles
UMIRRTXT	Without mirror text
UETSBOX	Without engine tunnel storage
UREFRIG	Without refrigerator
USIGN	Without front cab sign
XINS-CAB	One extra layer of cab insulation
UGUARDW	Without windscreen stone guard

Miscellaneous

Variant	Description
UFFEND	Without fenders on second front axle
URFCAR	Without rear fender carrier
RMUDF-AS	Rear mudflaps with anti-spray on all rear axle fenders
RFEND-B	Rear 3 piece fenders with anti-spray function (all rear axles)
FWP0475	Fifth wheel (king pin) position 475 mm before centre of first drive axle
5WM-LPRO	Fifth wheel mounting on 8 mm Volvo L-profiles
5WH230	Fifth wheel leg-height 230 mm
KPSIZE50	King pin size 50 mm (2 inches)
5WT-SH	SAF-Holland/+GF+ SK-S 36.20 V cast iron fixed fifth wheel
URAMP	Without sliding members/protection members
UTOWTYPE	Without towing member
UTOWMBR	Without towing member
UCOUPLIN	Without towing coupling
UTOWR	Without rear towing device
WHC-FOL2	2 foldable wheel chocks
RDECK	Basic rear deck (one plate between frame rails and one over left fuel tank or left battery box)
UTAIL	Without tail lift preparation
UHPG	Without gearbox mounted hydraulic pump
UFFTP	Without second front axle fender top height
UNIF-TRA	Basic tractor vehicle
ULCHF	Without load carrier
ULCL	Without load carrier length
RFC-1	Fender and front underrun calculation following EC legal requirements
RFH-BAS	Optimal fender installation (rear and 2nd front axle)
5WLM-L	Low fifth wheel maintenance with plastic top plate
FACT-BEL	Final assembly plant Belgium
10500MM	Frame length 10500 mm
CHAGH-BL	Black chassis grab handles
UCHAINS	Without snow chains
UTMP	Without towing member position
UFFQP	Without second front axle quarter fender mounting position
UCROSSRE	Without cross reinforcement for swapbody
U5WLUB	Without fifth wheel lubrication
UTCIND	Without trailer connection indication
UHBAT	Without holes for body attachments
UHOOKSC	Without snow chain hooks
UPSCAT	Without propeller shaft catcher
UCRANEPK	Without crane plates
SDC1	Steering demand calculation according to ECE regulation R79
UFBA	Without front body attachments
URBA	Without lower rear body attachments
UHPE	Without engine mounted hydraulic pump
WHCP-F	Wheel chock(s) in the front part of the vehicle

List of warnings/errors (1 message):



20011

(1)

The specification contains unauthorized kola variants for the product type (FM 42 T):
10500MM, WTD-DUAL

No restrictions violated

Application version: 155, EDB library version: 341.0.2 Elapsed: 2.17 seconds Built: May 9 2019, 15:30:43